



TEST ITEM	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	DIMENSION E	Striking Voltage(1-2/4-3)
UNIT	mm	mm	mm	mm	mm	KV
TEST CONDITION	/	/	/	/	/	/
SPEC	55.5MAX	29.5MAX	14.0MAX	23.3±0.3	4.0±0.5	2.1
USL	55.500	29.5	14.0	23.60	4.50	
LSL				23.00	3.50	
1	54.42	28.69	12.53	23.13	3.92	OK
2	54.42	28.70	12.52	23.21	4.12	OK
3	54.42	28.62	12.54	23.16	4.13	OK
4	54.42	28.68	12.52	23.18	4.05	OK
5	54.49	28.65	12.51	23.20	4.13	OK
6	54.43	28.72	12.60	23.24	4.09	OK
7	54.51	28.71	12.54	23.20	4.08	OK
8	54.47	28.69	12.66	23.18	4.11	OK
9	54.40	28.61	12.57	23.20	4.04	OK
10	54.42	28.71	12.55	23.24	4.08	OK
11	54.34	28.70	12.54	23.19	3.97	OK
12	54.40	28.69	12.52	23.17	4.07	OK
Average	54.43	28.68	12.55	23.19	4.07	
Judgment	OK	OK	OK	OK	OK	

INSPECTION ITEM		AOL	RESULT	USION  ACCEPTED REJECTED  WE CERTEIFY THAT ALL PRODUCTS HAD PASSED HI-POT TEST.
1	IR	Maj	OK	
2	ELEC.CHARATERISTICS	Maj	OK	
3	MECHANICAL DIMENSION	Maj	OK	
4	APPEARANCE	Min	OK	
5	MARKING TMS94819CT . A 126450 D	Maj	OK	
6	TERMINAL PULL TEST	Min	/	
7	OPERATING TORQUE	Maj	/	
8	SOLDERABILITY	Maj	/	
9	PACKING	Maj	OK	
10	HI-POT: P-S 2.0KVac 3mA 2S 50Hz	Cri	OK	
	P-C 2.0KVac 3mA 2S 50Hz	Cri	OK	
	S-C 3.5KVac 3mA 2S 50Hz	Cri	OK	
Checked By		Prepared By		TEST CONDITION TEMPERATURE 25°C HUMIDITY: 70%RH