


HER201 THRU HER208

HIGH EFFICIENCY RECTIFIERS

Reverse Voltage - 50 to 1000 Volts Forward Current - 2.0 Amperes



Dimensions in inches and (millimeters)

FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ High speed switching for high efficiency
- ◆ Low reverse leakage
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed: 250°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

MECHANICAL DATA

Case: JEDEC DO-15 molded plastic body

Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS MARKING	HER 201	HER 202	HER 203	HER 204	HER 205	HER 206	HER 207	HER 208	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	300	400	600	800	1000	VOLTS
Maximum RMS voltage	V _{RMS}	35	70	140	210	280	420	560	700	VOLTS
Maximum DC blocking voltage	V _{DC}	50	100	200	300	400	600	800	1000	VOLTS
Maximum average forward rectified current 0.375”(9.5mm) lead length at TA=50°C	I _(AV)	2.0								Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	50.0								Amps
Maximum instantaneous forward voltage at 2.0A	V _F	1.0			1.3		1.70			Volts
Maximum DC reverse current TA=25°C	I _R	5.0								uA
at rated DC blocking voltage TA=100°C		100.0								
Maximum reverse recovery time (NOTE 1)	t _{rr}	50					75			ns
Typical junction capacitance (NOTE 2)	C _J	30.0					20.0			pF
Typical thermal resistance (NOTE 3)	R _{qJA}	50.0								°C/W
Operating junction and storage temperature range	T _J ,T _{STG}	-55 to +125								°C

Note: 1. Reverse recovery condition I_F=0.5A, I_R=1.0A, I_{rr}=0.25A

2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

RATINGS AND CHARACTERISTIC CURVES HER201 THRU HER208

