



SPECIFICATION

Current Rating:1 Amp
 Withstanding Voltage:500V AC For 1 Minute
 △ Insulation Resistance:1000 Megaohms Min.
 △ Contact Resistance:20 Milliohms Max.
 Operation Temperature:-40°C~+105°C
 Insulator:PBT+G.F.(UL94V-0)
 △ Contact:Brass,Selective Gold Flash
 Over Nickel
 RoHS Compliant

MFC 20 XX T - H
 (1) (2) (3) (4) (5)

- (1) MFC:2.0 IDC Socket For 1.0mm Flat Cable
- (2) 20:Without S.R.
- (3) XX:No. Of Position
- (4) T:Tray Packing
- (5) H:RoHS Compliant

Pin	A	B	C
6	11.20	5.00	4.00
8	13.20	7.00	6.00
10	15.20	9.00	8.00
12	17.20	11.00	10.00
14	19.20	13.00	12.00
16	21.20	15.00	14.00
18	23.20	17.00	16.00
20	25.20	19.00	18.00
24	29.20	23.00	22.00
26	31.20	25.00	24.00
30	35.20	29.00	28.00
34	39.20	33.00	32.00
40	45.20	39.00	38.00
44	49.20	43.00	42.00
50	55.20	49.00	48.00
60	65.20	59.00	58.00

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.3 .X ±0.2 .XX ±0.1 .XXX ±0.05
PART No. MFC20XXT-H		MEI		
DRAWING No. MFC20XXT-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		
REV.	A2	UNIT mm		

NO.	REV.	REVISIONS	CHK	DATE
△A2		Modify Data	HZF	08/31/2016
△A1		Modify Data	HZF	03/11/2013
△A0		NEW RELEASE	HZF	04/29/2012