



ELECTRICAL:

1. Rate Voltage / Current: 250V / 10A
2. Normal Electric Strength: Between Housing (Cover the silicone insulation Tube) and Lead, Dielectric Strength should be AC 50hz, 1500V, Last 1 mins without Blink and Breakdown.
3. Insulation Resistance: Between housing (Cover the silicone insulation Tube and Lead Insulation Resistance > 2MΩ
4. Contact Insulation between Lead ≤ 0.028Ω
5. Disconnecton Insulation Resistance: Lead to lead in disconnection, Insulation Resistance ≥ 0.2MΩ
6. Leadkage Current: ≤ 0.2mA

How to Order:

RY- 250V- 10A (TF XX)

Rated Function Temperature

Available Temperature Range 55 to 285.

YUHUI ELECTRONIC TECH. CO.,LTD.

GENERAL TOLERANCE

X.* ± 5.0°	X. ± 0.30
.X* ± 3.0°	.X ± 0.25
.XX* ± 2.0°	.XX ± 0.15
.XXX* ± 1.0°	.XXX ± 0.10

DESIGN: 黄 语 惠

CHECK: 忠 诚

AUDIT: 忠 诚

APPROVE: 忠 诚

DATE: 2020.02.28

DATE: 2020.03.02

DATE: 2020.03.02

DATE: 2020.03.02

DWG. NO.:

YH-RY-250V-10A-001A-001

PART NO.:

RY-250V-10A(TF142)

TITLE:

250V/10A, Steel Type Thermal Fuse

REV.: 01	UNIT.: mm	SCALE.: 1:1	PAGE.: 1/1	
--------------------	---------------------	-----------------------	----------------------	--