


Female TERMINAL




T-DS1069-S C 6 0 0 ①

Contact Plating
6: Tin

Female Terminal

Wire Range		O.D. of Wire
Section Area (mm ²)	AWG#	mm
0.08~0.33	28~22	1.2~1.9

Female Housing



N=No. of contact

I-DS1069-S C W 0 X ①

No. of contact
02~20

NOTES:

1. MAIN SPECIFICATIONS

- Housing material: NYLON 66
- Wire range: AWG#28~#22
- Rated voltage: 250V
- Rated current: 1A
- Contact resistance: $\leq 30\text{m}\Omega$
- Insulation resistance: $\geq 1000\text{M}\Omega$
- Withstanding voltage: 500V, AC 1 minute
- Temperature range: $-25 \sim +85^\circ\text{C}$
- Recommend PC board thickness: 1.6mm

2. PRODUCT NUMBER CODE:

DS1069 - X X X X X X X

Bend Type (R/A only)

A: Type A

B: Type B

Contact Type

X: W/O kink

S: W/ kink

Contact Plating

6: Tin

8: Full gold flash

Housing Color

W: White

Mounting type

V: V/T


R: Right Angle

Connector type

M: Male

No. of contact
2 to 20

Male V/T TYPE



Tel: 86-574-63508787

Fax: 86-574-63510817

E-mail: sale@connfly.com


http://www.connfly.com

Add: East Industry Zone KuangYan


Town Cixi Ningbo China

P.C: 315333


Male Right Angle



W/ kink




W/O kink



2-7(include) pins

Type A

Type B



All of pins

N=No. of contact

GENERAL TOLERANCE

X. ± 0.60
.X ± 0.38
.XX ± 0.25

ANGLE TOLERANCE

X. $\pm 5^\circ$
.X $\pm 3^\circ$
.XX $\pm 2^\circ$

PROJECTION



TITLE

P.C.B CONNECTOR 2.5mm XH TYPE

UNITS

mm

SHEET SIZE

A4

SERIES

DS1069 SERIES

DRAWING TYPE

CUSTOMER

SCALE

1:1

SHEET

1 OF 1

DRAWING NO.

C-DS1069-XXXXX-D



晨翔电子有限公司

CONNFLY CONNFLY ELECTRONIC CO. LTD