



PCB LAYOUT

Material
Housing: PA66,UL94V-0
Cage: Iron,Ni plated
Pin Header: Iron 0.8T,Tin plated
Screw: M2.5,steel Zn plated

Electrical
Rated voltage: 300V
Rated current: 10A
Contact Resistance: 20 mΩ
Insulation resistance: 500MΩ/DC500V
Withstand voltage: AC2000V / 1min
Wire Range: 24~12AWG 2.5mm²

Mechanical
Temp. Range: -40 °C ~ +105 °C
Strip length: 6~7mm
Torque: 0.4Nm (3.6Lb.in)

Order Information

L-KLS2-103-5.00-XXP-2 S 00

RoHS
 Terminal Block
 Pitch
 No.: of Pole
 Color: 2-Blue 4- Green
 Screw:SC=Composit slot screws (+ -)
 S-Slot Screw C-Crass Screw
 Product Code: 00~99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ±0.60		X. ±5°		Screw CONN TERM Block 5.00mm	
.X ±0.38		.X ±3°		KLS P/N:	L-KLS2-103-5.00-XXP-2S
.XX ±0.25		.XX ±2°			
Draw by	2015-09-01	PROJECTION		NingBo KLS ELECTRONIC CO.,L TD.	
Check by	2015-09-15	UNITS	mm		
SCALE		SHEET SIZE	A4		